

IEEE JOURNAL OF
**SOLID-STATE
CIRCUITS**

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



JUNE 2011

VOLUME 46

NUMBER 6

IJSCBC

(ISSN 0018-9200)

New Associate Editors *U. Moon* 1235

REGULAR PAPERS

Analysis and Design of Small-Signal Polar Transmitters for Cellular Applications	<i>H. Darabi, H. Jensen, and A. Zolfaghari</i>	1237
Analysis and Design of D-Band Injection-Locked Frequency Dividers	<i>B.-Y. Lin and S.-I. Liu</i>	1250
A Wideband Millimeter-Wave Frequency Synthesis Architecture Using Multi-Order Harmonic-Synthesis and Variable N -Push Frequency Multiplication	<i>M. M. Abdul-Latif, M. M. Elsayed, and E. Sánchez-Sinencio</i>	1265
A Supply-Rail-Coupled eTextiles Transceiver for Body-Area Networks	<i>P. P. Mercier and A. P. Chandrakasan</i>	1284
A 10.2 Mbps Pulse Harmonic Modulation Based Transceiver for Implantable Medical Devices	<i>F. Inanlou, M. Kiani, and M. Ghovanloo</i>	1296
A Frequency Synthesizer With Optimally Coupled QVCO and Harmonic-Rejection SSBmixer for Multi-Standard Wireless Receiver	<i>D. Huang, W. Li, J. Zhou, N. Li, and J. Chen</i>	1307
Low-Power CMOS Equalizer Design for 20-Gb/s Systems	<i>S. Ibrahim and B. Razavi</i>	1321
7.4 Gb/s 6.8 mW Source Synchronous Receiver in 65 nm CMOS	<i>M. Hossain and A. Chan Carusone</i>	1337
A Charge-Domain Auto- and Cross-Correlation Based Data Synchronization Scheme With Power- and Area-Efficient PLL for Impulse Radio UWB Receiver	<i>L. Liu, T. Sakurai, and M. Takamiya</i>	1349
A 10-bit, 40-MS/s, 1.21 mW Pipelined SAR ADC Using Single-Ended 1.5-bit/cycle Conversion Technique	<i>M. Furuta, M. Nozawa, and T. Itakura</i>	1360
A 14 bit 200 MS/s DAC With SFDR >78 dBc, IM3 < -83 dBc and NSD < -163 dBm/Hz Across the Whole Nyquist Band Enabled by Dynamic-Mismatch Mapping	<i>Y. Tang, J. Briaire, K. Doris, R. van Veldhoven, P. C. W. van Beek, H. J. A. Hegt, and A. H. M. van Roermund</i>	1371
A CMOS 4.35-mW +22-dBm IIP3 Continuously Tunable Channel Select Filter for WLAN/WiMAX Receivers	<i>M. Oskooei, N. Masoumi, M. Kamarei, and H. Sjöland</i>	1382
A Micropower Low-Noise Neural Recording Front-End Circuit for Epileptic Seizure Detection	<i>C. Qian, J. Parramon, and E. Sánchez-Sinencio</i>	1392
A 60 pW $g_m C$ Continuous Wavelet Transform Circuit for Portable EEG Systems	<i>A. J. Casson and E. Rodriguez-Villegas</i>	1406



An 847–955 Mb/s 342–397 mW Dual-Path Fully-Overlapped QC-LDPC Decoder for WiMAX System in 0.13 μm CMOS	<i>B. Xiang, D. Bao, S. Huang, and X. Zeng</i>	1416
A 100 pJ/bit, (32,8) CMOS Analog Low-Density Parity-Check Decoder Based on Margin Propagation	<i>M. Gu and S. Chakrabarty</i>	1433
A 3.6 μs Latency Asynchronous Frame-Free Event-Driven Dynamic-Vision-Sensor	<i>J. A. Leñero-Bardallo, T. Serrano-Gotarredona, and B. Linares-Barranco</i>	1443
CMOS Silicon Physical Unclonable Functions Based on Intrinsic Process Variability	<i>S. Stanzione, D. Puntin, and G. Iannaccone</i>	1456
A 10-MHz Green-Mode Automatic Reconfigurable Switching Converter for DVS-Enabled VLSI Systems	<i>C. Zheng and D. Ma</i>	1464
1.8 V Low-Transient-Energy Adaptive Program-Voltage Generator Based on Boost Converter for 3D-Integrated NAND Flash SSD	<i>K. Ishida, T. Yasufuku, S. Miyamoto, H. Nakai, M. Takamiya, T. Sakurai, and K. Takeuchi</i>	1478
An Energy Efficient V_{PP} Generator With Fast Ramp-Up Time for Mobile DRAM	<i>K.-Y. Kim, Y. Kim, D.-C. Lee, Y.-R. Kang, H. Kim, S.-W. Kim, and J. Park</i>	1488
A 3T Gain Cell Embedded DRAM Utilizing Preferential Boosting for High Density and Low Power On-Die Caches ...	<i>K. C. Chun, P. Jain, J. H. Lee, and C. H. Kim</i>	1495
PATENT ABSTRACTS		1506

IT IS with
Gabriel Rin
zerbe to the J
They add to the
with profession
academia.
Dr. Floyd ha
millimeter-wa
Rincón-Mora
record with en
Digital Object I



(ISSCC) and
technical adv
winner of the
computer sc
Winner Awa



design" (2
CIRCUITS
ciety (SSC
and Syste
tems (MV