

APPLIED THERMAL ENGINEERING

DESIGN · PROCESSES · EQUIPMENT · ECONOMICS

Volume 30, Issues 17–18

December 2010

CONTENTS

- | | | |
|---|------|---|
| M. BOUDOUH, H. L. GUALOUS and M. DE LABACHELERIE | 2619 | Local convective boiling heat transfer and pressure drop of nanofluid in narrow rectangular channels |
| H.-C. CHENG, Y.-H. TSAI, K.-N. CHEN and J. FANG | 2632 | Thermal placement optimization of multichip modules using a sequential metamodeling-based optimization approach |
| R. BAYÓN, E. ROJAS, L. VALENZUELA, E. ZARZA and J. LEÓN | 2643 | Analysis of the experimental behaviour of a 100 kW _{th} latent heat storage system for direct steam generation in solar thermal power plants |
| H. MEHLING, S. HIEBLER and E. GÜNTHER | 2652 | New method to evaluate the heat storage density in latent heat storage for arbitrary temperature ranges |
| O. AYDIN and Y. E. BOKE | 2658 | An experimental study on carbon monoxide emission reduction at a fire tube water heater |
| X. F. GAO, C. W. ZHANG, J. J. WEI and B. YU | 2663 | Performance prediction of an improved air-cooled steam condenser with deflector under strong wind |
| B. YU, C. LI, Z. ZHANG, X. LIU, J. ZHANG, J. WEI, S. SUN and J. HUANG | 2670 | Numerical simulation of a buried hot crude oil pipeline under normal operation |
| S. JIAN, F. LIN and Z. SHIGANG | 2680 | Performance calculation of single effect absorption heat pump using LiBr + LiNO ₃ + H ₂ O as working fluid |
| K. Y. LEONG, R. SAIDUR, S. N. KAZI and A. H. MAMUN | 2685 | Performance investigation of an automotive car radiator operated with nanofluid-based coolants (nanofluid as a coolant in a radiator) |
| K. SUKSANKRAISORN, S. PATUMSAWAD and B. FUNGTAMMASAN | 2693 | Co-firing of Thai lignite and municipal solid waste (MSW) in a fluidised bed: Effect of MSW moisture content |
| A. SATHEESH and P. MUTHUKUMAR | 2698 | Performance investigation of double-stage metal hydride based heat pump |
| X. LI, T. WANG and B. DAY | 2708 | Numerical analysis of the performance of a thermal ejector in a steam evaporator |

[continued on inside back cover]



1359-4311(201012)30:17-18;1-C



ELSEVIER

Indexed/Abstracted in: Appl. Mech. Rev., Res. Alert, Cam. Sci. Abstr., Chemical Abstracts Service, Curr. Cont./Eng. Tech. & Appl. Sci., Curr. Tech. Ind., EIC Intell., Eng. Ind., Metals Abstr., Curr. Cont. SCISEARCH Data., TCEA, Also covered in the abstract and citation database SCOPUS. Full text available on ScienceDirect

Printed by Polestar Wheatons Ltd, Exeter, UK

APPLIED THERMAL ENGINEERING

DESIGN · PROCESSES · EQUIPMENT · ECONOMICS

Volume 30, Issues 17–18

December 2010

CONTENTS—continued from outside back cover]

- | | | |
|---|------|--|
| B. KHANDELWAL and S. KUMAR | 2718 | Experimental investigations on flame stabilization behavior in a diverging micro channel with premixed methane–air mixtures |
| B. M. GOORTANI,
E. MATEOS-ESPEJEL and J. PARIS | 2724 | Integration of a cogeneration unit into a kraft pulping process |
| K. HWANG, C. H. SONG, K. SAITO
and S. KAWAI | 2730 | Experimental study on titanium heat exchanger used in a gas fired water heater for latent heat recovery |
| J. LI, S. WANG, W. CAI and
W. ZHANG | 2738 | Numerical study on air-side performance of an integrated fin and micro-channel heat exchanger |
| M. R. JAFARI NASR and R. BEHFAR | 2746 | A novel design for evaporative fluid coolers |
| J. SUN, L. FU, S. ZHANG and
W. HOU | 2753 | A mathematical model with experiments of single effect absorption heat pump using LiBr–H ₂ O |
| R. S. REDDY GORLA | 2763 | Probabilistic analysis of a liquefied natural gas storage tank |
| R. VENTAS, A. LECUONA,
M. LEGRAND and
M. C. RODRÍGUEZ-HIDALGO | 2770 | On the recirculation of ammonia-lithium nitrate in adiabatic absorbers for chillers |
| L. BAI, G. LIN and D. WEN | 2778 | Modeling and analysis of startup of a loop heat pipe |
| A. FASQUELLE, J. LE BESNERAIS,
S. HARMAND, M. HECQUET,
S. BRISSET, P. BROCHET and
A. RANDRIA | 2788 | Coupled electromagnetic acoustic and thermal-flow modeling of an induction motor of railway traction |
| J. F. MITRE, L. M. SANTANA,
R. B. DAMIAN, J. SU and
P. L. C. LAGE | 2796 | Numerical study of turbulent heat transfer in 3D pin-fin channels: Validation of a quick procedure to estimate mean values in quasi-periodic flows |
| L. FENG, Z. LIU and Y. LI | 2804 | Numerical study of methane and air combustion inside a small tube with an axial temperature gradient at the wall |
| D. LUNA, Y. JANNOT
and J.-P. NADEAU | 2808 | An oriented-design simplified model for the efficiency of a flat plate solar air collector |
| B. XIAO, Q. WANG, G. WANG,
R. D. SISSON Jr. and Y. RONG | 2815 | Robust methodology for determination of heat transfer coefficient distribution in convection |
| J. J. DEL COZ DÍAZ,
P. J. GARCÍA NIETO,
J. DOMÍNGUEZ HERNÁNDEZ and
F. P. ÁLVAREZ RABANAL | 2822 | A FEM comparative analysis of the thermal efficiency among floors made up of clay, concrete and lightweight concrete hollow blocks |
| S. WANG, Z. MA and D.-C. GAO | 2827 | Performance enhancement of a complex chilled water system using a check valve: Experimental validation |