

IEEE JOURNAL OF SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



MARCH 2010

VOLUME 45

NUMBER 3

IJSCBC

(ISSN 0018-9200)

A Compact Wideband CMOS Low Noise Amplifier With Gain Flatness Enhancement	502
..... <i>Y.-H. Yu, Y.-S. Yang, and Y.-J. E. Chen</i>	
A Current Reuse Quadrature GPS Receiver in 0.13 μm CMOS	510
..... <i>K.-W. Cheng, K. Natarajan, and D. J. Allstot</i>	
5–10 Gb/s 70 mW Burst Mode AC Coupled Receiver in 90-nm CMOS	524
..... <i>M. Hossain and A. Chan Carusone</i>	
A 0.6 V Zero-IF/Low-IF Receiver With Integrated Fractional-N Synthesizer for 2.4-GHz ISM-Band Applications	
..... <i>A. Balankutty, S.-Y. Yu, Y. Feng, and P. R. Kinget</i>	538
A 58–65 GHz Neutralized CMOS Power Amplifier With PAE Above 10% at 1-V Supply ...	554
..... <i>W. L. Chan and J. R. Long</i>	
High PSR Low Drop-Out Regulator With Feed-Forward Ripple Cancellation Technique	
..... <i>M. El-Nozahi, A. Amer, J. Torres, K. Entesari, and E. Sánchez-Sinencio</i>	565
A 7.1 mW, 10 GHz All Digital Frequency Synthesizer With Dynamically Reconfigured Digital Loop Filter in 90 nm CMOS Technology	578
..... <i>S.-Y. Yang, W.-Z. Chen, and T.-Y. Lu</i>	
A Low-Power Continuously-Calibrated Clock Recovery Circuit for UHF RFID EPC Class-1 Generation-2 Transponders	587
..... <i>C.-F. Chan, K.-P. Pun, K.-N. Leung, J. Guo, L.-K. L. Leung, and C.-S. Choy</i>	
A Time-Domain SAR Smart Temperature Sensor With Curvature Compensation and a 3σ Inaccuracy of $-0.4^\circ\text{C} \sim +0.6^\circ\text{C}$ Over a 0°C to 90°C Range	600
..... <i>P. Chen, C.-C. Chen, Y.-H. Peng, K.-M. Wang, and Y.-S. Wang</i>	
A 0.02-mm ² 9-Bit 50-MS/s Cyclic ADC in 90-nm Digital CMOS Technology	610
..... <i>Y.-C. Huang and T.-C. Lee</i>	
A 12 bit 50 MS/s CMOS Nyquist A/D Converter With a Fully Differential Class-AB Switched Op-Amp	
..... <i>Y.-J. Kim, H.-C. Choi, G.-C. Ahn, and S.-H. Lee</i>	620
An 80 mW 40 Gb/s 7-Tap $T/2$ -Spaced Feed-Forward Equalizer in 65 nm CMOS	629
..... <i>A. Momtaz and M. M. Green</i>	
All-Digital Circuits for Measurement of Spatial Variation in Digital Circuits	
..... <i>N. Drego, A. Chandrakasan, and D. Boning</i>	640
A 116 fps/74 mW Heterogeneous 3D-Media Processor for 3-D Display Applications	
..... <i>S.-H. Kim, H.-Y. Kim, Y.-J. Kim, K. Chung, D. Kim, and L.-S. Kim</i>	652
An Ultra-Low-Energy Multi-Standard JPEG Co-Processor in 65 nm CMOS With Sub/Near Threshold Supply Voltage ..	
..... <i>Y. Pu, J. Pineda de Gyvez, H. Corporaal, and Y. Ha</i>	668
<hr/>	
PATENTS ABSTRACTS	681
