

IEEE JOURNAL OF SOLID-STATE CIRCUITS

上海理工大学图书馆
军工路510号邮编:200093

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



AUGUST 2011

VOLUME 46

NUMBER 8

IJSCBC

(ISSN 0018-9200)

SPECIAL ISSUE ON THE 2010 IEEE CUSTOM INTEGRATED CIRCUITS CONFERENCE

Introduction to the Special Issue on the 2010 IEEE Custom Integrated Circuits Conference P. K. Hanumolu, R. Harjani, and A. L. S. Loke 1770

PAPERS

- A 4-Port-Inductor-Based VCO Coupling Method for Phase Noise Reduction Z. Deng and A. M. Niknejad 1772
- A 475 mV, 4.9 GHz Enhanced Swing Differential Colpitts VCO With Phase Noise of -136 dBc/Hz at a 3 MHz Offset Frequency T. W. Brown, F. Farhabakhshian, A. Guha Roy, T. S. Fiez, and K. Mayaram 1782
- An Efficient Mixed-Signal 2.4-GHz Polar Power Amplifier in 65-nm CMOS Technology D. Chowdhury, L. Ye, E. Alon, and A. M. Niknejad 1796
- Design and Analysis of Varactor-Less Interpolative-Phase-Tuning Millimeter-Wave LC Oscillators with Multiphase Outputs S. Rong and H. C. Luong 1810
- An Inside Body Power and Bidirectional Data Transfer IC Module Pair E. K. F. Lee 1820
- CMOS Technology Scaling Considerations for Multi-Gbps Optical Receivers With Integrated Photodetectors A. C. Carusone, H. Yasotharan, and T. Kao 1832
- A 6-Gb/s MIMO Crosstalk Cancellation Scheme for High-Speed I/Os T. Oh and R. Harjani 1843
- Fully Digital Transmit Equalizer With Dynamic Impedance Modulation R. Sredojević and V. Stojanović 1857
- A 0.7-to-3.5 GHz 0.6-to-2.8 mW Highly Digital Phase-Locked Loop With Bandwidth Tracking W. Yin, R. Inti, A. Elshazly, B. Young, and P. K. Hanumolu 1870
- A 550- μ W 10-b 40-MS/s SAR ADC With Multistep Addition-Only Digital Error Correction S.-H. Cho, C.-K. Lee, J.-K. Kwon, and S.-T. Ryu 1881
- SHA-Less Pipelined ADC With *In Situ* Background Clock-Skew Calibration P. Huang, S. Hsien, V. Lu, P. Wan, S.-C. Lee, W. Liu, B.-W. Chen, Y.-P. Lee, W.-T. Chen, T.-Y. Yang, G.-K. Ma, and Y. Chiu 1893
- Exploiting Combinatorial Redundancy for Offset Calibration in Flash ADCs G. Keskin, J. Proesel, J.-O. Plouchart, and L. Pileggi 1904
- A 5-MHz 11-Bit Self-Oscillating $\Sigma\Delta$ Modulator With a Delay-Based Phase Shifter in 0.025 mm² B. De Vuyst and P. Rombouts 1919
- A 5-MHz 91% Peak-Power-Efficiency Buck Regulator With Auto-Selectable Peak- and Valley-Current Control M. Du, H. Lee, and J. Liu 1928
- Fully-Integrated On-Chip DC-DC Converter With a 450X Output Range S. S. Kudva and R. Harjani 1940

