

IEEE JOURNAL OF SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



JULY 2011

VOLUME 46

NUMBER 7

IJSCBC

(ISSN 0018-9200)

SPECIAL ISSUE ON THE 36TH EUROPEAN SOLID-STATE CIRCUITS CONFERENCE (ESSCIRC)

Introduction to the Special Issue on the 36th European Solid-State Circuits Conference (ESSCIRC)	1519
..... A. Rodríguez-Vázquez, D. M. W. Leenaerts, and J. Pineda de Gyvez	

ANALOG AND DATA CONVERTERS

Active-RC Filters Using the Gm-Assisted OTA-RC Technique	1522
A 1.8 μ W 60 nV/ $\sqrt{\text{Hz}}$ Capacitively-Coupled Chopper Instrumentation Amplifier in 65 nm CMOS for Wireless Sensor Nodes	1534
A 65-nm CMOS Temperature-Compensated Mobility-Based Frequency Reference for Wireless Sensor Networks	1544
A Low-Power High-PSRR Clock-Free Current-Controlled Class-D Audio Amplifier	1553
A 7 mW 20 MHz BW Time-Encoding Oversampling Converter Implemented in a 0.08 mm ² 65 nm CMOS Circuit	1562
A 2.4 GS/s, Single-Channel, 31.3 dB SNDR at Nyquist, Pipeline ADC in 65 nm CMOS	1575
A 26 μ W 8 bit 10 MS/s Asynchronous SAR ADC for Low Energy Radios	1585

RF AND COMMUNICATIONS

A Flip-Chip-Packaged 25.3 dBm Class-D Outphasing Power Amplifier in 32 nm CMOS for WLAN Application	1596
A Low Phase Noise, Wideband and Compact CMOS PLL for Use in a Heterodyne 802.15.3c Transceiver	1606
A TX VCO for WCDMA/EDGE in 90 nm RF CMOS	1618
A Fully-Integrated, Short-Range, Low Data Rate FM-UWB Transmitter in 90 nm CMOS	1627



A 5 Mb/s UWB-IR Transceiver Front-End for Wireless Sensor Networks in 0.13 μm CMOS	1636
..... <i>S. Soldà, M. Caruso, A. Bevilacqua, A. Gerosa, D. Vogrig, and A. Neviani</i>	
A 2x2 MIMO Tri-Band Dual-Mode Direct-Conversion CMOS Transceiver for Worldwide WiMAX/WLAN Applications ...	1648
..... <i>K. Lim, S. Min, S. Lee, J. Park, K. Kang, H. Shin, H. Shim, S. Oh, S. Kim, J. Lee, C. Yoo, and K. Chun</i>	
A 40 nm CMOS 0.4–6 GHz Receiver Resilient to Out-of-Band Blockers	1659
..... <i>J. Borremans, G. Mandal, V. Giannini, B. Debaillie, M. Ingels, T. Sano, B. Verbruggen, and J. Craninckx</i>	

SENSORS, BIOMEDICAL APPLICATIONS AND ENERGY HARVESTING

A 160x120-Pixels Range Camera With In-Pixel Correlated Double Sampling and Fixed-Pattern Noise Correction	1672
..... <i>M. Perenzoni, N. Massari, D. Stoppa, L. Pancheri, M. Malfatti, and L. Gonzo</i>	
A 2.2 mA 4.3 mm ² ASIC for a 1000°/s 2-Axis Capacitive Micro-Gyroscope	1682
..... <i>L. Aaltonen, A. Kalanti, M. Pulkkinen, M. Paavola, M. Kämäräinen, and K. A. I. Halonen</i>	
A 0.12 mm ² 7.4 μW Micropower Temperature Sensor With an Inaccuracy of $\pm 0.2^\circ\text{C}$ (3σ) From -30°C to 125°C	1693
..... <i>K. Souri and K. A. A. Makinwa</i>	
An Integrated Stimulator With DC-Isolation and Fine Current Control for Implanted Nerve Tripoles	1701
..... <i>X. Liu, A. Demosthenous, and N. Donaldson</i>	
Monolithic Capacitive DC-DC Converter With Single Boundary–Multiphase Control and Voltage Domain Stacking in 90 nm CMOS	1715
..... <i>T. M. Van Breussegem and M. S. J. Steyaert</i>	
An Electro-Magnetic Energy Harvesting System With 190 nW Idle Mode Power Consumption for a BAW Based Wireless Sensor Node	1728
..... <i>H. Reinisch, S. Gruber, H. Unterassinger, M. Wiessflecker, G. Hofer, W. Pribyl, and G. Holweg</i>	

DIGITAL

An Energy-Efficient Biomedical Signal Processing Platform	1742
..... <i>J. Kwong and A. P. Chandrakasan</i>	
ASIC Implementation of Soft-Input Soft-Output MIMO Detection Using MMSE Parallel Interference Cancellation	1754
..... <i>C. Studer, S. Fateh, and D. Seethaler</i>	

Cont
with
held
ES
55.8
came
speci
2) the
by the
to sub
were
Pap
analog
agers,
and bi
and ar
duced

This
garajan
asitic c
grators
power c
order in
width, f
The r
lenges r
results in
mentatic
to achiev
120 dB F
a positiv
porate a
Sebastian
the elect
51 μW at
less than
A curren
by Torres
over the c
noise as l
peak effie
The su
65 nm CI
sampled