

APPLIED THERMAL ENGINEERING

DESIGN · PROCESSES · EQUIPMENT · ECONOMICS

Volume 30, Issue 13

September 2010

CONTENTS

- | | | |
|--|------|--|
| M. VERDE, L. CORTÉS,
J.M. CORBERÁN, A. SAPIENZA,
S. VASTA and G. RESTUCCIA | 1511 | Modelling of an adsorption system driven by engine waste heat for truck cabin A/C. Performance estimation for a standard driving cycle |
| B. ILLÉS | 1523 | Distribution of the heat transfer coefficient in convection reflow oven |
| E. NÆSS | 1531 | Experimental investigation of heat transfer and pressure drop in serrated-fin tube bundles with staggered tube layouts |
| L.C. SCHURT, C.J.L. HERMES and
A. TROFINO NETO | 1538 | Assessment of the controlling envelope of a model-based multivariable controller for vapor compression refrigeration systems |
| H. HASSAN, N. REGNIER,
C. PUJOS, E. ARQUIS and
G. DEFAYE | 1547 | Modeling the effect of cooling system on the shrinkage and temperature of the polymer by injection molding |
| J.-C. CHU, J.-T. TENG and
R. GREIF | 1558 | Experimental and numerical study on the flow characteristics in curved rectangular microchannels |
| C. DANG and E. HIHARA | 1567 | Numerical study on in-tube laminar heat transfer of supercritical fluids |
| T. LU, B. LIU, P.X. JIANG,
Y.W. ZHANG and H. LI | 1574 | A two-dimensional inverse heat conduction problem in estimating the fluid temperature in a pipeline |
| Z. ACEM, J. LOPEZ and
E. PALOMO DEL BARRIO | 1580 | KNO ₃ /NaNO ₃ – Graphite materials for thermal energy storage at high temperature: Part I. – Elaboration methods and thermal properties |
| J. LOPEZ, Z. ACEM and
E. PALOMO DEL BARRIO | 1586 | KNO ₃ /NaNO ₃ – Graphite materials for thermal energy storage at high temperature: Part II. – Phase transition properties |
| M. GADERER, G. GALLMETZER
and H. SPLIETHOFF | 1594 | Biomass fired hot air gas turbine with fluidized bed combustion |
| X. XU, L. XIA, M. CHAN and
S. DENG | 1601 | Inherent correlation between the total output cooling capacity and equipment sensible heat ratio of a direct expansion air conditioning system under variable-speed operation (XXG SMD SHR DX AC unit) |

[continued on inside back cover



ELSEVIER



1359-4311(201009)30:13;1-D

Indexed/Abstracted in: *Appl. Mech. Rev., Res. Alert, Cam. Sci. Abstr., Chemical Abstracts Service, Curr. Cont./Eng. Tech. & Appl. Sci., Curr. Tech. Ind., EIC Intell., Eng. Ind., Metals Abstr., Curr. Cont. SCISEARCH Data., TCEA, Also covered in the abstract and citation database SCOPUS®. Full text available on ScienceDirect®*

Printed by Polestar Wheatons Ltd, Exeter, UK

APPLIED THERMAL ENGINEERING

DESIGN · PROCESSES · EQUIPMENT · ECONOMICS

Volume 30, Issue 13

September 2010

CONTENTS—continued from outside back cover

- | | | |
|---|------|---|
| R. BORRAJO-PELÁEZ,
J. ORTEGA-CASANOVA and
J.M. CEJUDO-LÓPEZ | 1608 | A three-dimensional numerical study and comparison between the air side model and the air/water side model of a plain fin-and-tube heat exchanger |
| V.H. HERNÁNDEZ GÓMEZ,
D.M. GÁLVEZ and
J.L. FERNÁNDEZ ZAYAS | 1616 | Design recommendations for heat discharge systems in walls |
| K. OZDEMIR, A. HEPBASLI and
N. ESKIN | 1621 | Exergoeconomic analysis of a fluidized-bed coal combustor (FBCC) steam power plant |
| T. NAFFOUTI, J. ZINOUBI and
R.B. MAAD | 1632 | Experimental characterization of a free thermal plume and in interaction with its material environment |
| H. CAO and G. CHEN | 1644 | Optimization design of microchannel heat sink geometry for high power laser mirror |
| A. ROVIRA, M. VALDÉS and
M.D. DURÁN | 1652 | A model to predict the behaviour at part load operation of once-through heat recovery steam generators working with water at supercritical pressure |
| K.F. FONG, T.T. CHOW, C. LI,
Z. LIN and L.S. CHAN | 1659 | Effect of neutral temperature on energy saving of centralized air-conditioning systems in subtropical Hong Kong |
| P.K. NAGARAJAN, Y. MUKKAMALA
and P. SIVASHANMUGAM | 1666 | Studies on heat transfer and friction factor characteristics of turbulent flow through a micro-finned tube fitted with left-right inserts |
| S. EIAMSA-ARD and
P. PROMVONGE | 1673 | Thermal characteristics in round tube fitted with serrated twisted tape |
| A. HUSAIN and K.-Y. KIM | 1683 | Enhanced multi-objective optimization of a microchannel heat sink through evolutionary algorithm coupled with multiple surrogate models |
| S.K. HENNINGER, F.P. SCHMIDT
and H.-M. HENNING | 1692 | Water adsorption characteristics of novel materials for heat transformation applications |
| C.M. INVERNIZZI | 1703 | Stirling engines using working fluids with strong real gas effects |
| M. GHAZIKHANI, M.E. FEYZ and
A. JOHARCHI | 1711 | Experimental investigation of the Exhaust Gas Recirculation effects on irreversibility and Brake Specific Fuel Consumption of indirect injection diesel engines |
| S. GUNES, V. OZCEYHAN and
O. BUYUKALACA | 1719 | The experimental investigation of heat transfer and pressure drop in a tube with coiled wire inserts placed separately from the tube wall |
| S. MAO, Z. FENG and
E.E. MICHAELIDES | 1726 | Off-highway heavy-duty truck under-hood thermal analysis |
| J.L. SILVEIRA, C.E. TUNA,
W. DE QUEIROZ LAMAS and
I. APARECIDA DE CASTRO
VILLELA | 1734 | A contribution for thermoeconomic modelling: A methodology proposal |

[continued on last page

H. YIN, M. QU and D.H. ARCHER	1741	Model based experimental performance analysis of a microscale LiBr-H ₂ O steam-driven double-effect absorption Chiller
J.V. HERRERA, O. GARCÍA-VALLADARES, V.H. GÓMEZ and R. BEST	1751	Numerical simulation and experimental results of horizontal tube falling film generator working in a NH ₃ -LiNO ₃ absorption refrigeration system
R. KUMAR and M.A. ROSEN	1764	Thermal performance of integrated collector storage solar water heater with corrugated absorber surface
G. BOURKE and P. BANSAL	1769	Energy consumption modeling of air source electric heat pump water heaters
M. ZENG, L.H. TANG, M. LIN and Q.W. WANG	1775	Optimization of heat exchangers with vortex-generator fin by Taguchi method
P.H.D. SANTOS, E. BAZZO, S. BECKER, R. KULENOVIC and R. MERTZ	1784	Development of LHPs with ceramic wick
X. KANG, Q. LIAO, X. ZHU and Y. YANG	1790	Non-equilibrium extrapolation method in the lattice Boltzmann simulations of flows with curved boundaries (non-equilibrium extrapolation of LBM)
W.M. SONG, J.A. MENG and Z.X. LI	1797	Numerical study of air-side performance of a finned flat tube heat exchanger with crossed discrete double inclined ribs
L.W. WANG, Z. TAMAINOT-TELTO, S.J. METCALF, R.E. CRITOPH and R.Z. WANG	1805	Anisotropic thermal conductivity and permeability of compacted expanded natural graphite
L. CECCHINATO, M. CORRADI and S. MINETTO	1812	A critical approach to the determination of optimal heat rejection pressure in transcritical systems
X. FANG and Q. DAI	1824	Modeling of turbine mass flow rate performances using the Taylor expansion
A. BAHADORI and H.B. VUTHALURU	1832	Estimation of performance of steam turbines using a simple predictive tool
J. LU, X. LU, H. LIU, H. WANG and H. HE	1839	Calculation and analysis of dissipation heat loss in large-scale circulating fluidized bed boilers
X. LI, F. ZHONG, X. FAN, X. HUAI and J. CAI	1845	Study of turbulent heat transfer of aviation kerosene flows in a curved pipe at supercritical pressure
E.M. ISHIYAMA, A.V. HEINS, W.R. PATERSON, L. SPINELLI and D.I. WILSON	1852	Scheduling cleaning in a crude oil preheat train subject to fouling: Incorporating desalter control
J.-C. SHYU, C.-S. WEI, C.-J. LEE and C.-C. WANG	1863	Investigation of bubble effect in microfluidic fuel cells by a simplified microfluidic reactor
S. MAIKOWSKE, J.J. BRANDNER and R. LANGE	1872	A novel device for the optical investigation of phase transition in micro channel array evaporators